

HTX Blocks

Fiddle



PART NO	SHEAVE Ø	WORKING LOAD LIMIT		WEIGHT	
		Kg	lb	g	oz
20106031	50	800	1762	165	5.8
20106031	60	1100	2422	257	9.0
20107231	72	2000	4405	530	18.5

Fiddle & Becket



PART NO	SHEAVE Ø	WORKING LOAD LIMIT		WEIGHT	
		Kg	lb	g	oz
20106034	50	800	1762	175	6.1
20106034	60	1100	2422	289	9.6
20107234	72	2000	4405	560	19.6

Fiddle & Cam



PART NO	SHEAVE Ø	WORKING LOAD LIMIT *		WEIGHT	
		Kg	lb	g	oz
20106037	50	800	1762	335	11.7
20107237	72	2000	4405	768	25.2

* Block WLL, cleat WLL shown on the right

Fiddle, Becket & Cam



PART NO	SHEAVE Ø	WORKING LOAD LIMIT *		WEIGHT	
		Kg	lb	g	oz
20106039	50	800	1762	365	12.1
20106039	60	1100	2422	460	16.1
20107239	72	2000	4405	775	27.2


* Block WWL, cleat WLL shown on the right

Shackle Post Dimensions



	POST DIAMETER		TO FIT MAX PIN Ø	
	mm	In	mm	In
50mm HTX	9.6	$\frac{3}{8}$	5	$\frac{1}{4}$
60mm HTX	11.9	$\frac{7}{16}$	6	$\frac{1}{4}$
72mm HTX	16.5	$\frac{5}{8}$	9.8	$\frac{3}{8}$
90mm HTX	19.8	$\frac{3}{4}$	10	$\frac{3}{8}$

Line Size



	MAX LINE SIZE	
	mm	In
50mm HTX	10	$\frac{3}{8}$
60mm HTX	12	$\frac{1}{2}$
72mm HTX	14	$\frac{7}{16}$
90mm HTX	16	$\frac{5}{8}$

Cleat Used



	USE CLEAT	WORKING LOAD LIMIT	
		Kg	lb
50mm HTX	20104100BK	120	264
60mm HTX	20104110BK	180	396
72mm HTX	-	230	507

For more info refer to page 180

Suitable Traveller Upstand



	FIT TRAVELLER UPSTAND
50mm HTX	Size 1 NTR
60mm HTX	Size 1 HTX
72mm HTX	Size 2 NTR and Size 2 HTX
90mm HTX	Size 3 NTR

Pad Eyes



Wide range of pad eyes available, refer to page 152 for more information