


Stainless Steel Portlight

With its highly polished stainless outer frame, the Stainless Portlight will really shine on your boat. The handles and hinge system were designed to leave the lens clear of obstructions, giving it an uncluttered view and a clean, modern look.


- ABS Plastic Trim
- Can be installed with sealant or closed cell PVC tape
- Easily fitted by clamping the cabin sides between inner and outer frame with screws provided that are fastened into the outer frame
- Trim with clean styling




Lewmar Stainless Steel Portlight fitted to Bavaria 43, © 2011 Bavaria Yachtbau GmbH




Size 0




Size 1




Size 1RE




Size 7RE



Size 8



Round 250mm




Round 296mm

Stainless Steel Portlight




© 2011, Bavaria Yachtbau GmbH

Standard Portlight Dimensions



Cut-out Dimensions



Stainless Steel Portlight Specifications

PART NUMBER	SIZE	TRIM COLOUR	VERSION	OVERALL DIMENSIONS								CUT-OUT DIMENSIONS						PORTLIGHT WEIGHT		ACRYLIC WINDOW THICKNESS	
				X		Y		Z		R		X1		Y1		R1					
				mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	kg	lb
393020262	0	White	Opening	176	6 15/16	323	12 11/16	4	5/32	62.0	2 7/16	156	6 1/8	303	12	52.0	2 1/16	1.5	3.30	8	1/2
393010262	0	White	Fixed	176	6 15/16	323	12 11/16	4	5/32	62.0	2 7/16	156	6 1/8	303	12	52.0	2 1/16	1.5	3.30	10	3/8
393120262	1	White	Opening	191	7 1/2	367	14 7/16	4	5/32	62.0	2 7/16	171	6 3/4	347	13 5/8	52.0	2 1/16	1.7	3.80	8	1/2
393110262	1	White	Fixed	191	7 1/2	367	14 7/16	4	5/32	62.0	2 7/16	171	6 3/4	347	13 5/8	52.0	2 1/16	1.7	3.80	10	3/8
393180262	1RE	White	Opening	191	7 1/2	367	14 7/16	4	5/32	95.5	3 3/4	171	6 3/4	347	13 5/8	85.5	3 3/8	1.7	3.74	10	3/8
393170262	1RE	White	Fixed	191	7 1/2	367	14 7/16	4	5/32	95.5	3 3/4	171	6 3/4	347	13 5/8	85.5	3 3/8	1.7	3.74	10	3/8
393780262	7RE	White	Opening	191	7 1/2	425	16 3/4	4	5/32	95.5	3 3/4	171	6 3/4	405	15 15/16	85.5	3 3/8	1.9	4.18	10	3/8
393770262	7RE	White	Fixed	191	7 1/2	425	16 3/4	4	5/32	95.5	3 3/4	171	6 3/4	405	15 15/16	85.5	3 3/8	1.9	4.18	10	3/8
393820862	8	Chrome	Opening	196	7 11/16	452	17 13/16	4	5/32	n/a	n/a	See drawing on website						1.9	4.18	10	3/8
393810862	8	Chrome	Fixed	196	7 11/16	452	17 13/16	4	5/32	n/a	n/a	See drawing on website						1.9	4.18	10	3/8

1. Maximum hull thickness 30mm
2. Minimum hull thickness 9mm
3. All portlights are supplied with M5 x 20 screws for hull thickness 12-17mm
4. Portlights should be fitted to a flat surface +/-1mm
5. Complete with Flyscreen

Round Stainless Steel Portlight Specifications

PART NUMBER	TRIM COLOUR	VERSION	OVERALL DIAMETER		CUT-OUT DIAMETER		WEIGHT		THICKNESS	
			mm	in	mm	in	kg	lb	mm	in
30209800	Chrome	Opening	250	9 7/8	See website		1.4	3	10	3/8
30209900	Chrome	Opening	296	11 5/8	See website		2.0	4	10	3/8

1. Maximum hull thickness 24mm
2. Minimum hull thickness 8mm
3. All portlights are supplied with M5 x 12 fastenings
4. Portlights should be fitted to a flat surface +/-1mm
5. No Flyscreen is available for the Round Stainless Portlight

